



Part Number: 5116

5116 thin client

The 5116 is both powerful and flexible. Powered by a 1 GHz processor, this XPe unit is available with a wide assortment of legacy ports including PS2, Parallel and Serial ports.

This light weight thin client features internal 802.11 b/g/n wireless and supports wide screen.



✓ XPe Operating System	✓ Centralised Management
✓ Small Form Factor for Space-Saving	✓ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 and Cisco Compliant
✓ Multiple Level Lock Down Feature with Protected File System	✓ Wide Screen Support
✓ IE6 (**7/8 available upon request)	✓ 1600 X1200 Maximum Resolution
✓ Supports RDP, ICA and VDI Deployment	✓ Built-in Kensington Security Lock
✓ Energy Efficient (only 14 Watts)	✓ RoHS Compliant
✓ BOSaNOVA Secure 5250 Emulation	✓ WES (XPe SP3 available upon request)
✓ Citrix/VMware Ready	✓ Touch Screen Support

**Reduce IT Costs,
Increase Security
and Improve
Efficiency by
Switching to 10ZiG
Thin Clients**





System

Operating System	XPe (Windows Embedded Standard 2009 optional)
Form Factor	Compact case
Management	10ZiG Management Software
Processor	VIA C7 1GHz/ VIA CN700+VT8237R Plus
Browser	IE7 (IE8 STD with WES 2009 Build)
Wide Screen Support	●
Video Resolution	Up to 1600 x 1200 x 32 bit color

Memory

RAM (Stand/MAX)	512MB/512MB
Storage (Stand/MAX)	512MB/2GB

Software Configuration

Host Access (BOSaNOVA Secure)	Supports TN5250e, SSL and SSO
--------------------------------------	-------------------------------

ICA	Version 11 with HDX
RDP	6.1 (RDP 7 available on WES)

Client Software

Adobe Acrobat Viewer
Adobe Flash Player
MS Office Viewers 2003 (2007 available upon request)
Microsoft Outlook Express
Windows Media Player
Shockwave
Sun JVM & MS Java
VNC Shadowing

VDI Clients	Optional Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer
--------------------	--

Dimensions

Device	1.7" W x 9.4" H x 8.9" D 43mm x 240mm x 225mm
---------------	--

Weight	4.2 lbs. (1.9kg)
---------------	------------------

Audio

Mic In/Line Out	●
Speaker	x 1 (built-in 1W internal Speaker)

Management

10ZiG Remote Manager	●
Various Client Configurations	●
Shadow Terminals	●
Status Indication	●
Power on, Log off, Reboot and Shut down	●
Task Scheduler	●
Cloning of Terminals	●
Group Operations	●
Configuration of Various Connection Types including 5250	●
Update of Firmware	●

Ports

USB Ports Type 2	x4
PS2 Port	x2 (for keyboard & mouse)
Parallel Port	x1
Serial Port	x1
Video	x1 VGA

Environmental

Operating Temperature	0° ~ 35°C 32° ~ 95°F
Operating Humidity	20% ~ 80% non-condensing

Power

Consumption	14 watts average
AC/DC Adapter	Included

Networking

Autosensing, 10/100 Ethernet, RJ-45, WakeOnLAN, PXE boot, 802.11 b/g/n wireless optional

Compliance

RoHS, CE, FCC, BSMI

Features

Security Features	Kensington Security Lock Slot Auto start/auto-restart connection, Lock-down user interface
--------------------------	---

Language Support	US, UK English, German, French, Swedish and others by request
-------------------------	---

Ordering Information

PID	Description
5116NE	5116, XPe, IE7 SP3, Sun JVM & MS Java, RDP, ICA, Shockwave, Flashplayer, Optical Mouse, Adobe Acrobat Viewer, MS Office Viewers, MS Outlook Express and Windows Media Player.
5116	Featured software from 5116NE plus BOSaNOVA Secure 5250 Emulation
9010	Internal Wireless 802.11b/g/n
MS001	Optical Mouse
8122b	122-Key Driverless PC Keyboard
8104b	104-Key PC Keyboard

