



Part Number: 5402

5402 thin client

Value Class Thin Client

The 5402 is an affordable, energy efficient, compact thin client. This unit weighs just over 1lb. allowing flexible mounting options and low shipping costs. The 5402 has no moving parts, consumes only 8-9 watts of energy and also has Fast Boot for half the normal boot up time.

The 5402 supports three modes of operation:

WBT Mode	Windows based Terminal mode, where the terminal behaves like a CE.NET device with full screen applications, GUI 5250/3270, Terminal Server access, Citrix or VDI which auto start and auto-reconnect.
Desktop Mode	Windows Vista type user interface provides access to all applications in a windowing environment.
Kiosk Mode	Dedicated Kiosk type of interface not configurable by the user of the terminal.



**Reduce IT Costs,
Increase Security
and Improve
Efficiency by
Switching to 10ZiG
Thin Clients**

✓ Linux Operating System	✓ Centralised Management
✓ Small Form Factor for Space-Saving	✓ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 Personal/Enterprise
✓ Read Only File System	✓ Wide Screen Support
✓ Embedded Firefox Browser	✓ 1600 X1200 Maximum Resolution
✓ Supports RDP, ICA and VDI Deployment	✓ Built-in Kensington Security Lock
✓ Energy Efficient (Only 8-9W)	✓ RoHS Compliant
✓ TN5250e/TN3270e with Split Screen	✓ Energy Star Compliant
✓ VESA Mounting Capability	✓ Cisco VPN





System	
Operating System	Linux 2.6 Kernel
Form Factor	Compact case
Management	10ZiG Management Software
Processor	VIA Eden 500MHz
Browser	Firefox 3.0
Video Resolution	Up to 1600 x 1200 x 32 bit color
Wide Screen Support	•
Memory	
RAM (Stand/MAX)	256MB/1GB
Storage (Stand/MAX)	512MB/1GB
Software Configuration	
Host Access	Supports TN5250e, TN3270e, PuTTY with optional Ericom Power Term.
ICA	Version 11 with HDX
RDesktop	1.6
Client Software	Adobe Acrobat Reader Adobe Flash Player Sun JMM VNC Shadowing Cisco VPN Thunderbird Email Linux PN Agent NX Client X Windows
VDI Clients:	Quest vWorkspace , Leostream, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer
Dimensions	
Device	14" W x 6.1" H x 4.8" D 36mm x 156 mm x 122 mm
Weight	1.7 lbs. (0.75kg)
Audio	
Mic In/Line Out	•
Speaker	x 1 (built in 1W internal Speaker)
Management	
10ZiG Remote Manager	•
Various Client Configurations	•
Shadow Terminals	•
Status Indication	•
Power on, Log off, Reboot and Shut down	•
Task Scheduler	•
Cloning of Terminals	•
Group Operations	•
Configuration of Various Connection Types including 5250	•
Update of Firmware	•

Ports	
USB Ports	Type 2 x4
PS2 Port	•
Environmental	
Operating Temperature	0° ~ 35°C 32° ~ 95°
Operating Humidity	20% ~ 80% non condensing
Power	
Consumption	8 9 watts average
AC/DC Adapter	Included
Networking	
	Autosensing, 10/100 Ethernet, RJ 45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option
Compliance	
	RoHS WEEE CE FCC Energy Star Compliant
Features	
Security Features	Kensington Security Lock Slot Auto start/auto restart connection, Lock down user interface
Language Support	US, UK English, German, French, Swedish and others by request

Ordering Information	
PID	Description
5402	RBT 402, Linux,RDP, ICA,TN5250e, TN3270e, VDI Clients and Optical Mouse
9001	USB to Centronics
9004	VESA Mounting Bracket (with short VGA cable)
9010	Internal Wireless (b/g/n)
8009	OpenOffice Suite and Java Cache
8122b	122 Key Driverless PC Keyboard
8104b	104 Key PC Keyboard

