



Part Number: 5416v

5416v thin client

Value Class Thin Client

The 5416v Thin Client is designed for a desktop virtualisation (VDI) environment. Complete with VMware View with PCoIP, Citrix XenDesktop, 2X VirtualDesktopServer, Quest/Provision Networks vWorkspace, Leostream Connection Broker, Ericom PowerTerm WebConnect and kaviza VDI-In-A-Box, this unit offers increased flexibility and a complete desktop experience.

The 5416v is an affordable, energy efficient, compact thin client. This unit weighs just over 1lb. allowing flexible mounting options and low shipping costs. The 5416v has no moving parts and consumes only 8-9 watts of energy.



**Reduce IT Costs,
Increase Security
and Improve
Efficiency by
Switching to 10ZiG
Thin Clients**



| | |
|---|---|
| ✓ WES (XPe SP3) 2009 | ✓ Centralised Management |
| ✓ Small Form Factor for Space-Saving | ✓ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 and Cisco Compliant |
| ✓ Multiple Level Lock Down Feature with Protected File System | ✓ Wide Screen Support |
| ✓ IE8 | ✓ 1600 X 1200 Maximum Resolution |
| ✓ Supports RDP, ICA and VDI Deployment | ✓ Built-in Kensington Security Lock |
| ✓ Energy Efficient (Only 8-9 Watts) | ✓ RoHS and Engery Star Compliant |
| ✓ Designed for Virtual Desktop Deployment | ✓ VESA Mounting Capability |



System

| | |
|----------------------------|----------------------------------|
| Operating System | WES (XPe SP3) 2009 |
| Form Factor | Compact case |
| Management | 10ZiG Management Software |
| Processor | VIA 500MHz |
| Browser | IE8 |
| Video Resolution | Up to 1600 x 1200 x 32 bit color |
| Wide Screen Support | • |

Memory

| | |
|----------------------------|-----------|
| RAM (Stand/MAX) | 512MB/1GB |
| Storage (Stand/MAX) | 1GB/1GB |

Software Configuration

| | |
|------------------------|---|
| ICA | Version 12.1 with HDX |
| RDP | 7 |
| Client Software | Windows Media Player Adobe Flash Player Shockwave Sun JVM & MS Java VNC Shadowing |
| VDI Clients | Quest vWorkspace , Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP, 2X VirtualDesktopServer and Kaviza VDI In A Box |

Dimensions

| | |
|---------------|---|
| Device | 14" W x 6.1" H x 4.8" D 36mm x 156 mm x 122 mm |
| Weight | 1.7 lbs. (0.75kg) |

Audio

| | |
|------------------------|------------------------------------|
| Mic In/Line Out | • |
| Speaker | x 1 (built in 1W internal Speaker) |

Management

| | |
|--|---|
| 10ZiG Remote Manager | • |
| Various Client Configurations | • |
| Shadow Terminals | • |
| Status Indication | • |
| Power on, Log off, Reboot and Shut down | • |
| Task Scheduler | • |
| Cloning of Terminals | • |
| Group Operations | • |
| Update of Firmware | • |
| Recover Image | • |

Ports

| | | |
|------------------|--------|----|
| USB Ports | Type 2 | x4 |
| PS2 Port | | • |

Environmental

| | |
|------------------------------|--------------------------|
| Operating Temperature | 0° ~ 35°C 32° ~ 95°F |
| Operating Humidity | 20% ~ 80% non condensing |

Power

| | |
|----------------------|-------------------|
| Consumption | 8 9 watts average |
| AC/DC Adapter | Included |

Networking

| | |
|--|---|
| | Autosensing, 10/100 Ethernet, RJ 45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option |
|--|---|

Compliance

| | |
|--|-----------------------|
| | RoHS |
| | WEEE |
| | CE |
| | FCC |
| | Energy Star Compliant |

Features

| | |
|--------------------------|---|
| Security Features | Kensington Security Lock Slot Auto start/auto restart connection, Multiple level lock down user interface Administrative and user passwords |
| Language Support | US, UK English, German, French, Swedish and others by request |

Ordering Information

| PID | Description |
|--------------|--|
| 5416v | 5416v, XPe, IE8, RDP, ICA, Flash Player, Shockwave, Windows Media Player, Sun JVM & MS Java, VDI Clients and Optical Mouse |
| 9001 | USB to Centronics |
| 9004 | VESA Mounting Bracket (with short VGA cable) |
| 9010 | Internal Wireless (802.11 b/g/n + Cisco) |
| 8104b | 104 Key PC Keyboard |

