



Part Number: 5466

# 5466 thin client

## Value Class Thin Client

The 5466 is an affordable, energy efficient, compact thin client. This unit weighs just over 1lb. allowing flexible mounting options and low shipping costs. The 5466 has no moving parts, consumes only 8-9 watts of energy and also has Fast Boot for half the normal boot up time.



The 5466 supports three modes of operation:

<b>WBT Mode</b>	Windows based Terminal mode, where the terminal behaves like a CE.NET device with full screen applications, GUI 5250/3270, Terminal Server access, Citrix or VDI which auto start and auto-reconnect.
<b>Desktop Mode</b>	Windows Vista type user interface provides access to all applications in a windowing environment.
<b>Kiosk Mode</b>	Dedicated Kiosk type of interface not configurable by the user of the terminal

**Reduce IT Costs,  
Increase Security  
and Improve  
Efficiency by  
Switching to 10ZiG  
Thin Clients**

✓ Linux Operating System	✓ Centralised Management
✓ Small Form Factor for Space-Saving	✓ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 Personal/Enterprise
✓ Read Only File System	✓ Wide Screen Support
✓ Embedded Firefox Browser	✓ 1600 X1200 Maximum Resolution
✓ Supports RDP, ICA and VDI Deployment	✓ Built-in Kensington Security Lock
✓ Energy Efficient (Only 8-9W)	✓ RoHS Compliant
✓ TN5250e/TN3270e with Split Screen	✓ Energy Star Compliant
✓ VESA Mounting Capability	✓ Cisco VPN





## System

<b>Operating System</b>	Linux 2.6 Kernel
<b>Form Factor</b>	Compact case
<b>Management</b>	10ZiG Management Software
<b>Processor</b>	VIA Eden 500MHz
<b>Browser</b>	Firefox 3.0
<b>Video Resolution</b>	Up to 1600 x 1200 x 32 bit color
<b>Wide Screen Support</b>	•

## Memory

<b>RAM (Stand/MAX)</b>	256MB/1GB
<b>Storage (Stand/MAX)</b>	512MB/512MB

## Software Configuration

<b>Host Access</b>	Supports TN5250e, TN3270e, PuTTY with optional Ericom Power Term.
<b>ICA</b>	Version 11 with HDX
<b>RDesktop</b>	1.6
<b>Client Software</b>	Adobe Acrobat Reader Adobe Flash Player Sun JVM VNC Shadowing Cisco VPN Thunderbird Email Linux PN Agent NX Client X Windows
<b>VDI Clients:</b>	Quest vWorkspace, Leostream, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer

## Dimensions

<b>Device</b>	14" W x 6.1" H x 4.8" D 36mm x 156 mm x 122 mm
---------------	---

<b>Weight</b>	1.7 lbs. (0.75kg)
---------------	-------------------

## Audio

<b>Mic In/Line Out</b>	•
<b>Speaker</b>	x 1 (built in 1W internal Speaker)

## Management

<b>10ZiG Remote Manager</b>	•
<b>Various Client Configurations</b>	•
<b>Shadow Terminals</b>	•
<b>Status Indication</b>	•
<b>Power on, Log off, Reboot and Shut down</b>	•
<b>Task Scheduler</b>	•
<b>Cloning of Terminals</b>	•
<b>Group Operations</b>	•
<b>Configuration of Various Connection Types including 5250</b>	•
<b>Update of Firmware</b>	•

## Ports

<b>USB Ports Type 2</b>	x4
<b>PS2 Port</b>	•

## Environmental

<b>Operating Temperature</b>	0° ~ 35°C 32° ~ 95°F
<b>Operating Humidity</b>	20% ~ 80% non condensing

## Power

<b>Consumption</b>	8 9 watts average
<b>AC/DC Adapter</b>	Included

## Networking

	Autosensing, 10/100 Ethernet, RJ 45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option
--	---

## Compliance

	RoHS
	WEEE
	CE
	FCC
	Energy Star Compliant

## Features

<b>Security Features</b>	Kensington Security Lock Slot Auto start/auto restart connection, Lock down user interface
<b>Language Support</b>	US, UK English, German, French, Swedish and others by request

## Ordering Information

PID	Description
<b>5466</b>	5466, Linux, VDI Clients, RDP, ICA, TN5250e and TN3270e
<b>MS001</b>	Optical Mouse
<b>9001</b>	USB to Centronics
<b>9004</b>	VESA Mounting Bracket (with short VGA cable)
<b>9010</b>	Internal Wireless (b/g/n)
<b>8009</b>	OpenOffice Suite and Java Cache
<b>8122b</b>	122 Key Driverless PC Keyboard
<b>8104b</b>	104 Key PC Keyboard

