



Part Number: 5616v

5616v thin client

Performance Class Thin Client

The 5616v Thin Client is designed for a desktop virtualisation (VDI) environment. Complete with VMware View with PCoIP, Citrix XenDesktop, 2X VirtualDesktopServer, Quest vWorkspace, Leostream Connection Broker, Ericom PowerTerm Web Connect and Kaviza VDI-In-A-Box, this unit offers a complete desktop experience.

The 5616v is the fastest, small form factor thin client on the market. This energy efficient unit boasts the Intel Atom N270 1.6 GHz Dual Thread processor offering exceptional performance and flexibility.



✓ WES (XPe SP3) 2009	✓ Centralised Management
✓ Small Form Factor for Space-Saving	✓ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 and Cisco Compliant
✓ Multiple Level Lock Down Feature with Protect File System	✓ Wide Screen Support
✓ IE8	✓ 1600 X1200 Maximum Resolution
✓ Supports RDP, ICA and VDI Deployment	✓ Built-in Kensington Security Lock
✓ Energy Efficient (only 12 Watts)	✓ RoHS Compliant
✓ Designed for Virtual Desktop Deployment	✓ Energy Star Compliant
✓ VESA Mounting Capability	✓ Dual Monitor Option

**Reduce IT Costs,
Increase Security
and Improve
Efficiency by
Switching to 10ZiG
Thin Clients**





System	
Operating System	WES (XPe SP3) 2009
Form Factor	Compact case
Management	10ZiG Management Software
Processor	Intel Atom N270 1.6GHz Dual Thread
Browser	IE8
Video Resolution	Up to 1600 x 1200
Wide Screen Support	•
Dual Monitor	Optional
Memory	
RAM (Stand/MAX)	512MB/1GB
Storage (Stand/MAX)	1GB/1GB
Software Configuration	
ICA	Version 12.1 with HDX
RDP	6.1
Client Software	Windows Media Player
	Adobe Flash Player
	Shockwave
	Sun JVM & MS Java
	VNC Shadowing
VDI Client	Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP, 2X VirtualDesktopServer and Kaviza VDI In A Box
Dimensions	
Device	1.4" W x 6.1" H x 4.8" D 36mm x 156 mm x 122 mm
Weight	1.7 lbs. (0.75kg)
Audio	
Mic In/Line Out	•
Speaker	x 1 (built in 1W internal Speaker)
Management	
10ZiG Remote Manager	•
Various Client Configurations	•
Shadow Terminals	•
Status Indication	•
Power on, Log off, Reboot and Shut down	•
Task Scheduler	•
Cloning of Terminals	•
Group Operations	•
Update of Firmware	•
Recover Image	•

Ports	
USB Ports	Type 2 x4
PS2 Port	•
Environmental	
Operating Temperature	0° ~ 35°C 32° ~ 95°F
Operating Humidity	20% ~ 80% non condensing
Power	
Consumption	12 watts average
AC/DC Adapter	Included
Networking	
	Autosensing, 10/100/1000 Ethernet, RJ 45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option
Compliance	
	RoHS
	WEEE
	CE
	FCC
	Energy Star Compliant
Features	
Security Features	Kensington Security Lock Slot Auto start/auto restart connection, Multiple level lock down user interface Administrative and user passwords
Language Support	US, UK English, German, French, Swedish and others by request
Ordering Information	
PID	Description
5616v	5616v, XPe, IE8, RDP, ICA, Flash Player, Shockwave, Windows Media Player, Sun JVM & MS Java, VDI Clients and Optical Mouse
9001	USB to Centronics
9006A	VESA Mounting Bracket (with DM DVI cable)
9006B	VESA Mounting Bracket (with DM VGA cable)
9007	Dual Monitor Option
9010	Internal Wireless (802.11 b/g/n + Cisco)
8104b	104 Key PC Keyboard

