



Part Number: 6702

6702 thin client

Elite Class Thin Client

The 6702 offers a combination of high performance and expandability. Powered by a VIA Nano processor, this unit is powerful, energy efficient and secure.

Designed for easy expansion and capable of rich multi-media graphics, the 6702 provides a superior end user experience and also offers Fast Boot for half the normal boot up time.

The **6702** supports three modes of operation:



**Reduce IT Costs,
Increase Security
and Improve
Efficiency by
Switching to 10ZiG
Thin Clients**

Desktop Mode	Windows Vista type user interface provides access to all applications in a windowing environment.
WBT Mode	Windows based Terminal mode, where the terminal behaves like a CE.NET device with full screen applications, GUI 5250/3270, Terminal Server access, Citrix or VDI which auto start and auto-reconnect.
Kiosk Mode	Dedicated Kiosk type of interface not configurable by the user of the terminal

✓ Linux Operating System	✓ Centralised Management
✓ No Moving Parts	✓ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 Personal/Enterprise
✓ Read Only File System	✓ Wide Screen Support
✓ Embedded Firefox Browser	✓ 1920 x 1080 Maximum Resolution
✓ Supports RDP, ICA and VDI Deployment	✓ Built-in Kensington Security Lock
✓ Energy Efficient	✓ RoHS Compliant
✓ TN5250e/TN3270e with Split Screen	✓ Dual Monitor Support
✓ Open Office & Skype	✓ Cisco VPN





System

Operating System	Linux 2.6 Kernel
Form Factor	Compact case
Management	10ZiG Management Software
Processor	VIA Nano 1.3 GHz
Browser	Firefox 3.0
Video Resolution	Up to 1920 x 1080 x 32 bit color
Wide Screen Support	•

Memory

RAM (Stand/MAX)	1GB/2GB
Storage (Stand/MAX)	512MB/16GB

Software Configuration

Host Access	Supports TN5250e, TN3270e, PuTTY with optional Ericom Power Term.
ICA	Version 11 with HDX
RDesktop	1.6
Client Software	Adobe Acrobat Reader Adobe Flash Player Sun JVM VNC Shadowing Cisco VPN Thunderbird Email Linux PN Agent NX Client X Window Skype Open Office
VDI Clients:	Quest vWorkspace, Leostream, Ericom PowerTerm WebConnect, VMware View with PCoIP and 2X VirtualDesktopServer

Dimensions

Device	22" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm
---------------	--

Weight	3.7 lbs. (1.7kg)
---------------	------------------

Audio

Mic In/Line Out	•
Speaker	x 1 (built in 1W internal Speaker)

Management

10ZiG Remote Manager	•
Various Client Configurations	•
Shadow Terminals	•
Status Indication	•
Power on, Log off, Reboot and Shut down	•
Task Scheduler	•
Cloning of Terminals	•
Group Operations	•
Configuration of Various Connection Types including 5250	•
Update of Firmware	•

Ports

USB Ports Type 2	6
PS2 Port	x2
Serial Port	1*
Parallel Port	1*
Video Ports	2 x DVI

Environmental

Operating Temperature	0° ~ 40°C 32° ~ 104°F
Operating Humidity	20% ~ 90% non condensing

Power

Consumption	14 watts average
AC/DC Adapter	Included

Networking

	Autosensing, 10/100/1000 Ethernet, RJ 45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option.
--	---

Compliance

	RoHS
	WEEE
	CE
	FCC

Features

Security Features	Kensington Security Lock Slot Auto start/auto restart connection, Lock down user interface
Language Support	US, UK English, German, French, Swedish and others by request

Ordering Information

PID	Description
6702	6702, Linux, Open Office, Skype, RDP, ICA, TN5250e, TN3270e and Optical Mouse
9011	PCI Expansion Card (Serial and Parallel port)
9010	Internal Wireless (b/g/n)
8122x	122 Key Driverless PC Keyboard
8104b	104 Key PC Keyboard

* One parallel and one serial port available with optional PCI card (9011)

