



Part Number: 6716v

6716v thin client

Elite Class Thin Client

The 6716v offers a combination of high performance and expandability. Powered by a VIA Nano processor, this unit is powerful, energy efficient and secure.

The 6716v is designed for a desktop virtualisation (VDI) environment. Complete with VMware View with PCoIP, Citrix XenDesktop, 2X VirtualDesktopServer, Quest vWorkspace, Leostream Connection Broker, Ericom PowerTerm Web Connect and Kaviza VDI-In-A-Box, this unit offers increased flexibility and a complete desktop experience.



✓ WES (XPe SP3) 2009	✓ Centralised Management
✓ No Moving Parts	✓ Optional Internal 802.11 b/g/n Wireless with WEP, WPA, WPA2 and Cisco Compliant
✓ Multiple Level Lock Down Feature with Protected File System	✓ Wide Screen Support
✓ IE8 Browser	✓ 1680 X 1200 Maximum Resolution
✓ Supports RDP, ICA and VDI Deployment	✓ Built-in Kensington Security Lock
✓ Energy Efficient	✓ Dual and Quad Monitor Support

**Reduce IT Costs,
Increase Security
and Improve
Efficiency by
Switching to 10ZiG
Thin Clients**





System

Operating System	WES (XPe SP3) 2009
Form Factor	Compact case
Management	10ZiG Management Software
Processor	VIA Nano 1.3 GHz
Browser	IE8
Video Resolution	Up to 1680 x 1200 x 32 bit color
Wide Screen Support	•
Monitor Support	Dual and Quad Monitor optional

Memory

RAM (Stand/MAX)	2GB/4GB
Storage (Stand/MAX)	2GB/16GB

Software Configuration

ICA	Version 12.1 with HDX
RDP	7
Client Software	Adobe Flash Player Windows Media Player Shockwave Sun JVM & MS Java VNC Shadowing
VDI Clients	Quest vWorkspace, Leostream, Citrix XenDesktop, Ericom PowerTerm WebConnect, VMware View with PCoIP, 2X VirtualDesktopServer and Kaviza VDI-In-A-Box

Dimensions

Device	2.2" W x 9" H x 8.2" L 57 mm x 230 mm x 210 mm
Weight	3.7 lbs. (1.7kg)

Audio

Mic In/Line Out	•
Speaker	x 1 (built-in 1W internal Speaker)

Management

10ZiG Remote Manager	•
Various Client Configurations	•
Shadow Terminals	•
Status Indication	•
Power on, Log off, Reboot and Shut down	•
Task Scheduler	•
Cloning of Terminals	•
Group Operations	•
Update of Firmware	•
Recover Image	•

Ports

USB Ports Type 2	6
PS2 Port	x2
Serial Port	1
Parallel Port	1***
Video Ports	2 x DVI

Environmental

Operating Temperature	0° ~ 40°C 32° ~ 104°F
Operating Humidity	20% ~ 90% non-condensing

Power

Consumption	14 watts average
AC/DC Adapter	Included

Networking

	Autosensing, 10/100/1000 Ethernet, RJ-45, WakeOnLAN, PXE boot, Internal 802.11 b/g/n wireless option,
--	---

Compliance

	RoHS
	WEEE
	CE
	FCC

Features

Security Features	Kensington Security Lock Slot Auto start/auto-restart connection, Multiple level lock-down user Administrative and user passwords
Language Support	US, UK English, German, French, Swedish and others by request

Ordering Information

PID	Description
6716v	6716v, WES (XPe SP3) 2009 Thin Client with Optical Mouse
9011	PCI Expansion Card (Serial and Parallel Port)
9010	Internal Wireless (802.11 b/g/n + Cisco)
8104b	104-Key PC Keyboard
8010	Quad Video support includes DVI & VGA Ports & 1GB DOM

*** One parallel and one serial port available with optional PCI card (9011)

